

Rim Guard™ Metric Tire Hydro-Flation Table 75% Full or Valve Level

Tire Size	Gal. of Rim Guard	Weight (lbs.)
240/70R16	8	86
250/80R16	12	128
250/80R18	13	139
250/95R34	24	257
250/95R50	32	342
260/70R18	10	107
260/80R20	15	161
290/95R34	34	364
290/90R38	34	364
320/70/R24	23	246
320/75R24	25	268
320/85R34	38	407
320/85R38	37	396
320/80R42	40	428
320/90R42	49	524
320/90R46	52	556
320/90R50	55	589
320/90R54	56	599
340/80R18	27	289
340/85R46	57	610
380/70R20	31	332
380/70R24	36	385
380/70R28	41	439
380/85R28	50	535
380/85R30	54	578
380/85R34	56	599
380/80R38	56	599
380/90R46	76	813
380/90R50	79	845
380/90R54	84	899
385/85R34MPT	60	642
420/70R24	47	503

420/70R28	53	567
420/80R46	86	920
420/85R28	66	706
420/90R30	72	770
460/70R28	71	760
460/70R30	75	803
480/70R34	83	888
480/80R38	105	1124
480/80R42	113	1209
480/80R46	119	1278
480/80R50	125	1338
480/85R34	99	1059
VA500/95D32	138	1477
520/85R38	133	1423
520/85R42	142	1520
520/85R46	153	1652
540/65R30	80	856
580/70R38	142	1520
600/65R28	99	1060
620/75R26	125	1338
620/70R42	169	1817
620/70R46	183	1967
650/75R32	162	1742
650/75R34	185	1989
650/85R38	229	2462
650/65R42	164	1763
710/70R38	201	2161
710/70R42	228	2451
750/65R26	168	1806
800/65R32	202	2172
800/70R38	265	2849
900/50R42	235	2526
900/60R32	270	2903
900/65R32	289	3107

Note: For 40% fill, multiply above values by 0.5.